



2400



[www.raycomfg.com](http://www.raycomfg.com)



**C100**  
Super Crawler

**General Specifications:**

<b>Weight</b>	
Tractor Only	11,340 lb (5,143 kg)
with Winch and Mulcher	14,190 lb (6,436.5 kg)
<b>Length</b>	
Tractor Only	128" (325.12 cm)
with Winch and Mulcher	185" (469.9 cm)
<b>Height</b>	99" (251.5 cm)
<b>Width</b>	
Tractor Only	71" (180 cm)
with Mulcher	82" (208.2" cm)
<b>Engine</b>	KUBOTA V3800 DI-T, 4 cylinder, turbo diesel, 99.2 hp (73.97 kW)
<b>Fuel</b>	40 gal (151.4 L)
<b>Hydraulic Tank</b>	24 gal (91 L)
<b>Track Shoe</b>	16" (40.64 cm) single grouser
<b>Rollers</b>	6 each side
<b>Hydraulic System</b>	39 gpm @ 5,500 psi, high flow pump (147.6 L/min @ 37,921 kPa)
<b>Ground Pressure</b>	
Tractor Only	4.6 psi (31.7 kPa)
with Winch and Mulcher	5.7 psi (39.3 kPa)
<b>Travel Speed High</b>	5.8 mph (9.3 km/h)
<b>Travel Speed Low</b>	3.3 mph (5.3 km/h)
<b>RAYCO Attachments</b>	PM638 Predator Mulching Head Winch or Skidder Winch Triple Grouser Steel Track LG-1 Grapple Rake
<b>Cab Certification Meets</b>	ROPS SAE J1040 FOPS SAE J231 OPS ISO 8084/WCB G603



**Purpose-Built...**

When you go into the woods, you need a machine you can count on. You need a loader-style mulching machine that's purpose-built from the ground up to be the most productive and reliable on the market today. The **C100** is that machine. It's equipped with a 99.2 hp Kubota engine and **RAYCO's** exclusive Super Flow closed loop, hydraulic system, providing 39 gal/minute at 5,500 psi to the Predator mulcher head.

To extend service intervals, the C100 features an advanced forestry cooling system which is easy to maintain and will extend service intervals, even when operating in the most extreme conditions. High capacity coolers allow operation in the hottest ambient temperatures. Debris screens filter out most of the contaminants that plug radiators and are easily removed for routine cleaning.

**Predator Mulcher**

<b>Weight</b>	2,350 lb (1,066 kg)
<b>Length</b>	42" (106.7 cm)
<b>Rotor Diameter</b>	16.75" (42.55 cm)
<b>Rotor Speed</b>	2,200 rpm
<b>Drive Belt</b>	Gates® Polychain GT
<b>Overall Width</b>	82" (208 cm)
<b>Cutting Width</b>	71.5" (182 cm)
<b>Teeth</b>	38

**C100:**

- 99.2 hp Kubota turbo-diesel
- 39 gal/min at 5,500 psi Super Flow hydraulics
- 16" steel tracks
- 3 escape routes in cab
- Forestry cooling package

**PM638 Predator Mulcher:**

- 38 double carbide tipped teeth
- Hydraulic pressure gauge
- Adjustable tree catcher
- Closed loop hydraulic system
- 71.5" cutting width, 82" overall width
- Mulching door



Roof Top Escape Hatch



Hydraulic Winch



Swing Open Rear Door

**Think Smart, Think Safe.....**

We care about your safety. When operating your RAYCO machinery always wear an approved helmet complete with ear muffs, face shield and the proper eyewear. Never operate under the influence of alcohol or drugs. Know your RAYCO, read and understand your owner's manual cover to cover.

C100

www.raycomfg.com

800.392.2686

**CALL TOLL FREE 800.392.2686**  
*(USA or Canada Only)*



**RAYCO Manufacturing, Inc.**

4255 E Lincoln Way  
Wooster, Ohio 44691-8601 USA  
Phone: 330.264.8699  
Fax: 330.264.3697  
raycomfg.com

SC-501-09/11 (replaces SC-501-11/08)  
Made and Printed in the USA

Copyright © 2008 RAYCO Manufacturing, Inc., Wooster, OH 44691

RAYCO Manufacturing Inc. retains the right to make changes in design and specifications; engineering; add or remove features; add improvements; or discontinue manufacturing at any time without notice or obligation.