

Visit our newly  
redesigned website!  
[www.raycomfg.com](http://www.raycomfg.com)

# Super Jr

with **SWING-out**  
controls



For 2011, Rayco is proud to introduce another industry first for compact stump cutters: the Super Jr series with swing-out operator control stations. The Super Jr line of compact, self-propelled stump cutters are now available with 3-position swing-out operator control stations to allow better visibility of the cutting action and easier travel through gates. The swing-out control is of particular value at times when visibility is crucial, such as grinding stumps near obstructions such as sidewalks or driveways. Novice operators will also have an easier time operating the swing-out control models efficiently, making this model perfect for rental stores. For travel through gates, the controls swing in-line with the machine so the operator can more easily drive through narrow openings. There are 2 grinding positions to allow operators the ability to select which position better suits the job conditions.



## RG1625 Super Jr & RG1635 Super Jr with Swing-Out Controls

<b>Model</b>	<b>RG 1625A Super Jr-S</b>	<b>RG 1635 Super Jr-S</b>
	<b>Gas Powered</b>	<b>Gas Powered</b>
<b>Weight - lb (kg)</b>	1,350 (612)	1,450 (657.7)
<b>Length - In (cm)</b>	108 (274.3)	108 (274.3)
<b>Height - In (cm)</b>	48.5 (123)	56 (142)
<b>Width - In (cm)</b>	34.5 (88)	34.5 (88)
<b>w/ Dual Wheels - In (cm)</b>	46 (117)	46 (117)
<b>Ground Drive</b>	Self-Propelled Hydraulic, Variable Speed	Self-Propelled Hydraulic, Variable Speed
<b>Engine - hp (kW)</b>	Kohler Command, 25 (18.4)	Vanguard V-Twin Big Block, 35 (26)
<b>Fuel Tank - gal (L)</b>	6.5 (24.6)	6.5 (24.6)
<b>Clutch</b>	Electromagnetic w/Wheel Brakes	Electromagnetic w/Wheel Brakes
<b>Super Tooth®</b>	18 total	18 total
<b>Cutter Wheel - In (cm)</b>	17.25 x .5 (43.8 x 1.3)	17.25 x 1 (43.8 x 2.5)
<b>Cutting Depth - In (cm)</b>	11 (28)	11 (28)
<b>Cutting Height - In (cm)</b>	26 (66)	26 (66)
<b>Cutting Width -In (cm)</b>	38 (97)	39 (99)
<b>Standard Features</b>	Electromagnetic Clutch	Electromagnetic Clutch
	Variable Travel Speed	2-Speed Travel
	Variable Swing Speed	Variable Swing Speed
	Hydraulic Steering	Hydraulic Steering



**Aux Chip Retainers**

[www.raycomfg.com](http://www.raycomfg.com) 800.392.2686



SP-2015/301S-TS-09/11 (replaces SP-2015/301S-TS-06/11)  
Made and Printed in the USA

Copyright © 2011 RAYCO Manufacturing, Inc., Wooster, OH 44691

RAYCO Manufacturing Inc. retains the right to make changes in design and specifications; engineering; add or remove features; add improvements; or discontinue manufacturing at any time without notice or obligation.