



Trailers



Wooster, OH

800-392-2686

www.raycomfg.com

Your solution to transporting your equipment.



TRSJR Trailer



The RAYCO TRSJR trailer is specifically designed to haul the self-propelled RG1635 Trac Jr, Super Jr stump cutter with single rear wheel plus any of the RAYCO Mini Work-Force line of handle bar stump cutters. The TRSJR trailer features a single pin lock to secure the stump cutter to the trailer. Standard features include electrostatic powder coat paint, skid resistant deck and ramps, and Dexter Torflex® Axle.

Weight - lb (kg)	620 (281)
Length - in (cm)	134 (340.4)
Width - in (cm)	62 (157.5) (outside fenders)
Height - in (cm)	28.5 (72.4) (top of fender)
	54 (137.2) (top of ramp)
GVWR - lb (kg)	2,960 (1342.6)
Wheels	13" ST185/13LRD Max capacity 1,725 lb @ 65 psi (671 kg @ 448.2 kPa) per tire Highway speed approved
Axle	Dexter TORFLEX #10 Low Profile (no brake)
Lighting	Right and left tail lights License plate lighting DOT approved
Hitch - in (cm)	2 (5.1) ball coupler with safety chains and hooks
Jack Stand - lb (kg)	2,000 (907) hand crank



TRSJRW Trailer



The RAYCO TRSJRW trailer is specifically designed to haul the self-propelled Super Jr stump cutter with dual rear wheels and can also be used to transport the RG1635 Trac Jr. The TRSJRW trailer features a single pin lock to secure the stump cutter to the trailer. Standard features include electrostatic powder coat paint, skid resistant deck and ramps, and Dexter Torflex® Axle.

Weight - lb (kg)	640 (290.3)
Length - in (cm)	134 (340.4)
Width - in (cm)	77 (195.6) (outside fenders)
Height - in (cm)	28.5 (72.4) (top of fender)
	54 (137.2) (top of ramp)
GVWR - lb (kg)	2,960 (1342.6)
Wheels	13" ST185/13LRD Max capacity 1,725 lb @ 65 psi (671 kg @ 448.2 kPa) per tire Highway speed approved
Axle	Dexter TORFLEX #10 Low Profile (no brake)
Lighting	Right and left tail lights License plate lighting DOT approved
Hitch - in (cm)	2 (5.1) ball coupler with safety chains and hooks
Jack Stand - lb (kg)	2,000 (907) hand crank



TRSJRWB Trailer



The RAYCO TRSJRWB trailer is equipped with electric brakes and is specifically designed to haul the self-propelled RG1645 stump cutter. The TRSJRWB can also be used to transport the RG1635 Trac Jr and any Super Jr series stump cutter with dual wheels. The TRSJRWB trailer features a single pin lock to secure the stump cutter to the trailer. Standard features include electrostatic powder coat paint, skid resistant deck and ramps, and Dexter Torflex® Axle with electric brakes.

Weight - lb (kg)	650 (294.8)
Length - in (cm)	134 (340.4)
Width - in (cm)	77 (195.6) (outside fenders)
Height - in (cm)	28.5 (72.4) (top of fender)
	54 (137.2) (top of ramp)
GVWR - lb (kg)	3,300 (1496.8)
Wheels	13" ST185/13LRD Max capacity 1,725 lb @ 65 psi (671 kg @ 448.2 kPa) per tire Highway speed approved
Axle	Dexter TORFLEX #10 Low Profile with Brake
Lighting	Right and left tail lights License plate lighting DOT approved
Hitch - in (cm)	2 (5.1) ball coupler with safety chains and hooks
Jack Stand - lb (kg)	2,000 (907) hand crank



TR100 Trailer



The RAYCO TR100 trailer is specifically designed to haul the RAYCO RG70, and RG100 self-propelled stump cutters. The TR100 features a single-pin lock to secure the stump cutter to the trailer. Standard features include: electrostatic powder-coat paint, skid-resistant deck and ramps, electric brakes and Tandem Dexter E-Z Lube suspension axle.

Weight - lb (kg)	1,300 (589.6)
Length - in (cm)	157 (398.7)
Width - in (cm)	76 (193) (outside fenders)
Height - in (cm)	32 (81.2) (top of fender)
	35 (88.9) (top of ramp)
GVWR - lb (kg)	7,000 (3175)
Wheels	700-15 Max capacity 2,156 lb @ 60 psi (977.94 kg @ 413.6 kPa) per tire (load range D) Highway speed approved
Axle - lb (kg)	Tandem Dexter E-Z Lube 3,500 (1587.5) rating each
Lighting	Right and left tail lights License plate lighting Side-marker lights DOT approved
Brake System - in (cm)	10 x 2.25 (25.4 x 5.7) electrical with trailer mounted breakaway safety switch and integral battery and charger (note: both axles have brakes)
Hitch - in (cm)	2 (5.1) ball coupler with safety chains and hooks
Optional Hitch	3" I.D. pintle hitch, 2 5/16" ball coupler
Jack Stand - lb (kg)	2,000 (907) hand crank (optional wheel available)





CALL TOLL FREE 800.392.2686
(USA or Canada Only)

RAYCO Manufacturing, Inc.

4255 E Lincoln Way
Wooster, Ohio 44691-8601 USA
Phone: 330.264.8699
Fax: 330.264.3697
raycomfg.com



Advantage![®]

www.gsaadvantage.gov

Contract # GS-30F-0021N

TR-101-11/11

Made and Printed in the USA

Copyright © 2011 RAYCO Manufacturing, Inc., Wooster, OH 44691

RAYCO Manufacturing Inc. retains the right to make changes in design and specifications; engineering; add or remove features; add improvements; or discontinue manufacturing at any time without notice or obligation. Equipment shown is for illustrative purposes only and may show optional accessories or components. For more information contact your RAYCO Dealer.