

## **FEATURES AND BENEFITS**

- 48-HP (36 kW) Isuzu 4LE2T Diesel Engine
- Telescoping boom
- Turf tires
- All steel plates
- Standard full-size skid steer attachment plate
- Low-pro suspension seat
- Hydraulic cooler / radiator combo with no additional electric fan



**MORBARK** 



## **4000AWL ARTICULATED LOADER** SPECIFICATIONS

General	US		Metric
Operating Height	88.56"		225 cm
Length (Loader Only)	134.5"		341.6 cm
Width	56.63"		143.8 cm
Ground Clearance	14.8"		37.6 cm
Max Lift Height (at hinge pin)	126.25"		320.7 cm
Weight*	10,985 lb		4,983 kg
*includes side weights, bumper v	weights, boom, ROPS,	and traction control	
Working Lift Capacity	4,000 lb		1814.4 kg
Engine Power	48 HP		36 kW
Engine Make and Type		Isuzu 4LE2T	
Fuel Type		Diesel	
Fuel Tank Capacity	14.5 gallons		54.88 L
Turf Tires		26 x 12.00 - 12	
Max Speed Low/High	6.5/13 MPH		10.46/20.9 k/h



Optional AG Tires provide more aggressive traction.



Low-pro suspension seating is protected by ROPS and FOPS guarding.



Standard telescoping boom provides excellent dumping and lifting height.

